



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FPB 14 SEL(40W) UV FR 8SEL(4000K).IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] Nick

[TESTLAB] Ningbo TengLi Testing Co., Ltd

[TESTDATE] 25 October 2019

[ISSUEDATE] 2019-10-25 14:51:21

[NEARFIELD]

[LAMPPOSITION] 0,0

[OTHER] EVERFINE GO-R5000_V2 SYSTEM

[MANUFAC] LumenFocus, LLC.

[LUMINAIRE] FPB 14 SEL(40W) UV FR 8SEL(4000K)

[OTHER]

[OTHER]	Gamma(deg)	Fz(lm)	Ft(lm)	%Lum	%Lamp
---------	------------	--------	--------	------	-------

[OTHER]	0- 10	118.06	118.06	3.20	3.20
---------	-------	--------	--------	------	------

[OTHER]	10- 20	339.44	457.51	12.39	12.39
---------	--------	--------	--------	-------	-------

[OTHER]	20- 30	517.91	975.41	26.43	26.43
---------	--------	--------	--------	-------	-------

[OTHER]	30- 40	629.66	1605.07	43.48	43.48
---------	--------	--------	---------	-------	-------

[OTHER]	40- 50	658.94	2264.01	61.34	61.34
---------	--------	--------	---------	-------	-------

[OTHER]	50- 60	601.01	2865.01	77.62	77.62
---------	--------	--------	---------	-------	-------

[OTHER]	60- 70	464.82	3329.83	90.21	90.21
---------	--------	--------	---------	-------	-------

[OTHER]	70- 80	276.39	3606.22	97.70	97.70
---------	--------	--------	---------	-------	-------

[OTHER]	80- 90	81.25	3687.47	99.90	99.90
---------	--------	-------	---------	-------	-------

[OTHER]	90-100	0.41	3687.87	99.91	99.91
---------	--------	------	---------	-------	-------

[OTHER]	100-110	0.39	3688.26	99.92	99.92
---------	---------	------	---------	-------	-------

[OTHER]	110-120	0.48	3688.74	99.94	99.94
---------	---------	------	---------	-------	-------

[OTHER]	120-130	0.47	3689.21	99.95	99.95
---------	---------	------	---------	-------	-------

[OTHER]	130-140	0.52	3689.72	99.96	99.96
---------	---------	------	---------	-------	-------

[OTHER]	140-150	0.50	3690.23	99.98	99.98
---------	---------	------	---------	-------	-------

[OTHER]	150-160	0.44	3690.66	99.99	99.99
---------	---------	------	---------	-------	-------

[OTHER]	160-170	0.32	3690.99	100.00	100.00
---------	---------	------	---------	--------	--------

[OTHER]	170-180	0.12	3691.11	100.00	100.00
---------	---------	------	---------	--------	--------

[OTHER]

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 14 SEL(40W) UV FR 8SEL(4000K).IES

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5092
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	127
Total Luminaire Watts	40
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.95 ft
Luminous Width (90-270)	0.95 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4705	4808	4749
55	4540	4664	4602
65	4270	4402	4360
75	3805	3951	3963
85	2793	3081	3359

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 14 SEL(40W) UV FR 8SEL(4000K).IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	631.16	N.A.	12.40
0-30	1345.65	N.A.	26.40
0-40	2214.31	N.A.	43.50
0-60	3952.49	N.A.	77.60
0-80	4975.04	N.A.	97.70
0-90	5087.12	N.A.	99.90
10-90	4924.25	N.A.	96.70
20-40	1583.15	N.A.	31.10
20-50	2492.2	N.A.	48.90
40-70	2379.44	N.A.	46.70
60-80	1022.54	N.A.	20.10
70-80	381.29	N.A.	7.50
80-90	112.09	N.A.	2.20
90-110	1.10	N.A.	0.00
90-120	1.76	N.A.	0.00
90-130	2.40	N.A.	0.00
90-150	3.81	N.A.	0.10
90-180	5.03	N.A.	0.10
110-180	3.93	N.A.	0.10
0-180	5092.15	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	162.88
10-20	468.29
20-30	714.49
30-40	868.66
40-50	909.05
50-60	829.13
60-70	641.25
70-80	381.29
80-90	112.09
90-100	0.56
100-110	0.53
110-120	0.66
120-130	0.64
130-140	0.71
140-150	0.70
150-160	0.60
160-170	0.45
170-180	0.17

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FPB 14 SEL(40W) UV FR 8SEL(4000K).IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	106	101	97	94	97	94	91	93	90	88	89	87	85	83
2	98	90	83	77	96	88	82	76	84	79	74	81	77	73	78	74	71	69
3	90	79	70	64	87	77	69	63	74	67	62	71	66	61	69	64	60	58
4	82	70	61	54	80	68	60	53	66	58	53	63	57	52	61	56	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	45	39	50	44	39	37
7	64	51	42	35	63	50	41	35	48	41	35	47	40	35	45	39	35	32
8	60	46	38	32	58	45	37	31	44	37	31	43	36	31	42	35	31	29
9	56	42	34	28	54	42	34	28	41	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	26	37	30	25	36	30	25	23


IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 14 SEL(40W) UV FR 8SEL(4000K).IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor Cavity		20	20	20	20	20	20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	17.4	19.1	17.8	19.4	19.7	17.5	19.2	17.9	19.5	19.8
	3H	19.3	20.8	19.6	21.1	21.5	19.4	20.9	19.8	21.2	21.6
	4H	19.9	21.4	20.3	21.7	22.1	20.1	21.5	20.5	21.9	22.3
	6H	20.5	21.8	20.9	22.2	22.5	20.7	22.0	21.1	22.4	22.7
	8H	20.6	21.9	21.1	22.3	22.7	20.9	22.1	21.3	22.5	22.9
	12H	20.7	21.9	21.2	22.3	22.8	21.0	22.2	21.4	22.6	23.0
4H	2H	18.1	19.5	18.5	19.9	20.2	18.2	19.6	18.6	20.0	20.4
	3H	20.2	21.4	20.6	21.8	22.2	20.3	21.5	20.7	21.9	22.3
	4H	21.0	22.1	21.4	22.5	22.9	21.2	22.2	21.6	22.7	23.1
	6H	21.6	22.6	22.1	23.0	23.5	21.9	22.8	22.3	23.2	23.7
	8H	21.8	22.7	22.3	23.2	23.6	22.1	23.0	22.5	23.4	23.9
	12H	22.0	22.8	22.5	23.3	23.7	22.3	23.1	22.7	23.6	24.0
8H	4H	21.3	22.2	21.8	22.7	23.1	21.5	22.4	22.0	22.8	23.3
	6H	22.1	22.8	22.6	23.3	23.8	22.3	23.1	22.8	23.6	24.0
	8H	22.4	23.0	22.9	23.6	24.0	22.7	23.3	23.2	23.8	24.3
	12H	22.6	23.2	23.1	23.7	24.2	22.9	23.5	23.4	24.0	24.6
12H	4H	21.4	22.2	21.8	22.6	23.1	21.6	22.4	22.0	22.8	23.3
	6H	22.2	22.8	22.7	23.3	23.8	22.4	23.1	23.0	23.6	24.1
	8H	22.5	23.1	23.0	23.6	24.1	22.8	23.4	23.3	23.9	24.4

Maximum UGR = 24.6

POLAR GRAPH



Maximum Candela = 1720.092 Located At Horizontal Angle = 90, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)