



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FPB 22 SEL(36W) UV FR 8SEL(5000K).IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] Nick

[TESTLAB] Ningbo TengLi Testing Co., Ltd

[TESTDATE] 27 December 2019

[ISSUEDATE] 2019-12-27 09:22:03

[NEARFIELD]

[LAMPPOSITION] 0,0

[OTHER] EVERFINE GO-R5000_V2 SYSTEM

[MANUFAC] LumenFocus, LLC.

[LUMINAIRE] FPB 22 SEL(36W) UV FR 8SEL(5000K)

[OTHER]

[OTHER]	Gamma(deg)	Fz(lm)	Ft(lm)	%Lum	%Lamp
---------	------------	--------	--------	------	-------

[OTHER]	0- 10	148.09	148.09	3.25	3.25
---------	-------	--------	--------	------	------

[OTHER]	10- 20	424.54	572.62	12.58	12.58
---------	--------	--------	--------	-------	-------

[OTHER]	20- 30	644.62	1217.24	26.75	26.75
---------	--------	--------	---------	-------	-------

[OTHER]	30- 40	779.45	1996.70	43.87	43.87
---------	--------	--------	---------	-------	-------

[OTHER]	40- 50	811.42	2808.12	61.70	61.70
---------	--------	--------	---------	-------	-------

[OTHER]	50- 60	736.96	3545.08	77.90	77.90
---------	--------	--------	---------	-------	-------

[OTHER]	60- 70	569.09	4114.17	90.40	90.40
---------	--------	--------	---------	-------	-------

[OTHER]	70- 80	338.65	4452.82	97.84	97.84
---------	--------	--------	---------	-------	-------

[OTHER]	80- 90	94.04	4546.86	99.91	99.91
---------	--------	-------	---------	-------	-------

[OTHER]	90-100	0.17	4547.02	99.91	99.91
---------	--------	------	---------	-------	-------

[OTHER]	100-110	0.34	4547.36	99.92	99.92
---------	---------	------	---------	-------	-------

[OTHER]	110-120	0.65	4548.00	99.93	99.93
---------	---------	------	---------	-------	-------

[OTHER]	120-130	0.79	4548.80	99.95	99.95
---------	---------	------	---------	-------	-------

[OTHER]	130-140	0.78	4549.58	99.97	99.97
---------	---------	------	---------	-------	-------

[OTHER]	140-150	0.62	4550.20	99.98	99.98
---------	---------	------	---------	-------	-------

[OTHER]	150-160	0.44	4550.64	99.99	99.99
---------	---------	------	---------	-------	-------

[OTHER]	160-170	0.33	4550.97	100.00	100.00
---------	---------	------	---------	--------	--------

[OTHER]	170-180	0.13	4551.10	100.00	100.00
---------	---------	------	---------	--------	--------

[OTHER]

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 22 SEL(36W) UV FR 8SEL(5000K).IES

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4551
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	127
Total Luminaire Watts	35.8
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	1.95 ft
Luminous Width (90-270)	1.95 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4142	4181	4246
55	3981	4028	4117
65	3736	3794	3912
75	3342	3429	3570
85	2365	2438	2788

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 22 SEL(36W) UV FR 8SEL(5000K).IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	572.62	N.A.	12.60
0-30	1217.24	N.A.	26.70
0-40	1996.7	N.A.	43.90
0-60	3545.08	N.A.	77.90
0-80	4452.82	N.A.	97.80
0-90	4546.86	N.A.	99.90
10-90	4398.77	N.A.	96.70
20-40	1424.07	N.A.	31.30
20-50	2235.49	N.A.	49.10
40-70	2117.47	N.A.	46.50
60-80	907.74	N.A.	19.90
70-80	338.65	N.A.	7.40
80-90	94.03	N.A.	2.10
90-110	0.50	N.A.	0.00
90-120	1.15	N.A.	0.00
90-130	1.94	N.A.	0.00
90-150	3.34	N.A.	0.10
90-180	4.24	N.A.	0.10
110-180	3.74	N.A.	0.10
0-180	4551.1	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	148.09
10-20	424.54
20-30	644.62
30-40	779.45
40-50	811.42
50-60	736.96
60-70	569.09
70-80	338.65
80-90	94.03
90-100	0.17
100-110	0.34
110-120	0.65
120-130	0.79
130-140	0.78
140-150	0.61
150-160	0.44
160-170	0.33
170-180	0.13

IES INDOOR REPORT

PHOTOMETRIC FILENAME : FPB 22 SEL(36W) UV FR 8SEL(5000K).IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	104	99	95	106	101	97	94	97	94	91	93	90	88	89	87	85	83
2	98	90	83	77	96	88	82	76	85	79	75	81	77	73	78	74	71	69
3	90	79	71	64	87	77	70	63	74	68	62	72	66	61	69	64	60	58
4	82	70	61	54	80	68	60	54	66	59	53	64	57	52	61	56	51	49
5	75	62	53	46	73	61	53	46	59	51	46	57	50	45	55	49	45	42
6	70	56	47	40	68	55	47	40	53	46	40	52	45	40	50	44	39	37
7	64	51	42	36	63	50	42	36	48	41	35	47	40	35	46	39	35	33
8	60	46	38	32	58	46	37	32	44	37	31	43	36	31	42	36	31	29
9	56	42	34	29	55	42	34	29	41	33	28	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	25	24


IES INDOOR REPORT
PHOTOMETRIC FILENAME : FPB 22 SEL(36W) UV FR 8SEL(5000K).IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	16.9	18.6	17.3	18.9	19.2	17.1	18.8	17.5	19.1	19.4
	3H	18.8	20.3	19.1	20.6	20.9	19.0	20.5	19.4	20.8	21.2
	4H	19.5	20.9	19.9	21.2	21.6	19.8	21.2	20.2	21.5	21.9
	6H	20.0	21.3	20.4	21.7	22.0	20.3	21.6	20.7	22.0	22.4
	8H	20.1	21.4	20.6	21.8	22.2	20.5	21.7	20.9	22.1	22.5
	12H	20.2	21.4	20.7	21.8	22.3	20.6	21.8	21.0	22.2	22.6
4H	2H	17.6	19.0	18.0	19.3	19.7	17.8	19.2	18.2	19.5	19.9
	3H	19.6	20.8	20.1	21.2	21.6	19.9	21.1	20.3	21.5	21.9
	4H	20.5	21.6	20.9	22.0	22.4	20.8	21.8	21.2	22.3	22.7
	6H	21.1	22.1	21.6	22.5	23.0	21.4	22.4	21.9	22.8	23.3
	8H	21.3	22.2	21.8	22.7	23.1	21.7	22.6	22.1	23.0	23.5
	12H	21.5	22.3	22.0	22.7	23.2	21.9	22.7	22.3	23.1	23.6
8H	4H	20.8	21.7	21.3	22.1	22.6	21.1	22.0	21.6	22.4	22.9
	6H	21.6	22.3	22.1	22.8	23.3	21.9	22.7	22.4	23.1	23.6
	8H	21.9	22.5	22.4	23.0	23.5	22.2	22.9	22.7	23.4	23.9
	12H	22.1	22.7	22.6	23.2	23.7	22.5	23.1	23.0	23.5	24.1
12H	4H	20.9	21.7	21.3	22.1	22.6	21.2	21.9	21.6	22.4	22.9
	6H	21.7	22.3	22.2	22.8	23.3	22.0	22.7	22.5	23.1	23.7
	8H	22.0	22.6	22.5	23.1	23.6	22.4	22.9	22.9	23.4	24.0

Maximum UGR = 24.1

POLAR GRAPH



Maximum Candela = 1564.85 Located At Horizontal Angle = 112.5, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (112.5 - 292.5) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)