



Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Cat. #: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

LED

## EMRW | LED Wet Location Emergency Unit w/ Remote Capacity

### Features:

- Ultra-bright, long life white LED lamp heads
- 15 LEDs per head (1.875 watt total per head)
- Dual 120/277V
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing
- 9.6V long life, maintenance free, rechargeable, NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Remote capacity of 3.7 watt standard in operating temperatures of 0°C - 50°C

### Mounting:

- Universal knockout pattern on back plate for wall mount. Snaps into place

### Ambient operating Temp.:

- -20°C to 50°C
- 0°C to 50°C for Remote Capacity

### Construction:

- Corrosion-resistant 5VA flame retardant UV-stabilized polycarbonate housing in gray or black finish
- Sealed and gasketed housing with hinged cover.
- Sealed and gasketed weather proof, adjustable lamp heads with high performance chrome-plated metallized reflector and tempered glass lenses for optimal light distribution

### Certifications:

- UL listed for wet locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes
- Certified to CEC under Title 20 Regulations (optional)



### Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see [www.LumenFocus.com](http://www.LumenFocus.com) for complete warranty terms and conditions



**Ordering Guide:**

example: EMRW DV B-CEC

Series	Voltage	Housing Color	-	Options
EMRW	DV		-	
<b>EMRW</b> Wet Location Emergency Unit w/ Remote Capacity	<b>DV</b> Dual 120/277V	<b>G</b> Gray  <b>B</b> Black		<b>Blank</b> None  <b>CEC</b> Title 20 Compliant

**Schematic:**

