

## IES ROAD REPORT

PHOTOMETRIC FILENAME : AMB MD 3 UV 850.IES

### DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002  
[TEST] R2DG210315050-S02  
[TESTLAB] BACL  
[TESTDATE] 2021-04-07  
[ISSUEDATE] 2021-04-07 21:06:58  
[LAMPPOSITION] 0,0  
[OTHER] EVERFINE GO-R5000\_V2 SYSTEM  
[MANUFAC] LumenFocus, LLC.  
[LUMCAT] AMB MD 3 UV 850  
[LAMP] N/A

### CHARACTERISTICS


IES Classification	Type III
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	26370
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	133
Total Luminaire Watts	198.1
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	8556.17
Maximum Candela Angle	270H 68V
Maximum Candela (<90 Degrees Vertical)	8556.17
Maximum Candela Angle (<90 Degrees Vertical)	270H 68V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	3805.2 (14.4% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

**IES ROAD REPORT**  
**PHOTOMETRIC FILENAME : AMB MD 3 UV 850.IES**

**LUMINAIRE CLASSIFICATION SYSTEM (LCS)**

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2442.1	N.A.	9.3
FM - Front-Medium (30-60)	8184.9	N.A.	31.0
FH - Front-High (60-80)	4530.8	N.A.	17.2
FVH - Front-Very High (80-90)	230.3	N.A.	0.9
BL - Back-Low (0-30)	2102.3	N.A.	8.0
BM - Back-Medium (30-60)	5772.0	N.A.	21.9
BH - Back-High (60-80)	3056.2	N.A.	11.6
BVH - Back-Very High (80-90)	51.4	N.A.	0.2
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	26370.0	N.A.	100.0
BUG Rating	B4-U0-G4		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	15388.1	58.4
Downward House Side	10981.9	41.6
Downward Total	26370.0	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	26370.0	100.0

POLAR GRAPH




Maximum Candela = 8556.17 Located At Horizontal Angle = 270, Vertical Angle = 68  
# 1 - Vertical Plane Through Horizontal Angles (270 - 90) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (68) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height  
 Values Based On 10 Foot Mounting Height  
 1/2 Maximum Candela Trace Shown As Dashed Curve  
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:  
Front: Low=2442.1, Medium=8184.9, High=4530.8, Very High=230.3  
Back: Low=2102.3, Medium= 5772.0, High=3056.2, Very High=51.4  
Uplight: Low=0.0, High=0.0

BUG Rating : B4-U0-G4