





ECLN 3 | LED Narrow Strip

Features:

- High performance LED technology
- 0-10V dimming drivers standard
- Field replaceable LED boards and drivers
- Frosted diffuser helps minimize glare and improve aesthetics
- Advanced controls available

Applications:

Suitable for most commercial and institutional applications

- Office
- Retail
- Coves
- Valences

Ambient Operating Temp.:

• -30°C to 40°C

Predicted L70 Lifetime:

- Up to 189,000 hrs (calculated) (L70 information for specific configurations available upon request)
- For BAA compliant configurations up to 189,000 hrs (calculated)

Construction:

- Precision brake formed from cold rolled steel
- Highly durable matte white finish. Optional matte black or metallic silver finish

Certifications:

 UL 1598 listed for US and Canada, suitable for damp locations



Warranty:

- 5 year limited system warranty see www.LumenFocus.com for complete warranty terms and conditions
- 10 year warranty option available on specific models Not available on all models. Certain conditions apply. Consult factory or sales representative for details.)











Ordering Guide:

example: ECL N 3 MD UV FR 840 QC B									FR 840 QC BK				
	Series	Width	Length	Output	Voltage	Shielding	CRI/CCT	Hanging	Controls	Options	Finish		
	ECL	Ν	3										
	ECL	N	3 36"	LW Low	UV 120-277	Blank No Lenses	835 80 CRI/3500K	Blank None	Blank No Controls	Blank No Options	Blank White		
				MD Medium	34 347V	FR Frosted Acrylic Diffusers	840 80 CRI/4000K 850 80 CRI/5000K	QC 10' Quick Hang Cable Kit	ZSOL Leviton Intellect Solo PIR Sensor ⁽¹⁾ Z211L_ Wattstopper FSP	EXT10 10-Year Extended Warranty(⁷⁾ C6 6' Single Circuit Cord	BK Matte Black SL Metallic Silver		
Notes (1) Max mounting height 10'. See Page 5 for more details. (2) "_" = lens type. See Page 5 for lens descriptions. (3) Max mounting height 49'. See Page 5 for more details. (4) Max mounting height 16.4'. See Page 4 for more details. (5) See Page 4 for more details.								Programmable Photo/Motion Multi-Voltage Sensor (high/ low/off) ⁽²⁾ Z311L_ Wattstopper FSP Bluetoothenabled Programmable Photo/Motion Multi-Voltage Sensor (high/low/off) ⁽²⁾ ZOSMD	C65W 6' Single Circuit Cord with Low Voltage Connections C10 10' Single Circuit Cord C105W 10' Single Circuit Cord with Low Voltage Connections				
	(6) Max mounting height 15'. See Page 4 for more details. (7) Not available on all models. Certain conditions apply.												

Controls Accessories (order separately)



For Douglas Controls

Consult factory or sales representative for details.

(9) "_" for 2-circuit wiring, specify circuit A or B here.

(8) EM1 and EM2: 120-277V / 0°C-50°C ambient.

Bluetooth 1 Zone Dimmer BT-DMSW-U-A BT-4BTSW-U-A Bluetooth 4-Button Wall Station Bluetooth 8-Button Wall Station BT-8BTSW-U-A



For Enlighted Controls

WS-2-00 (for Enlighted Connected & IoT) WS-2-00-IL



Enlighted Remote Control Wall Switch Enlighted Remote Control Wall Switch (for Enlighted One)

Douglas IFS sensor with dimming/occupancy/daylight harvesting and network capabilities⁽⁴⁾

Step-Dimming

(High/Low/Off)(3)

ZIFS

ZIFC

Douglas IFC controller with network capabilities⁽⁵⁾

ZENLO

Enlighted Micro Sensor with Dimming/Occupancy/Daylight Harvesting and Enlighted One System⁽⁶⁾

ZENLC

Enlighted Micro Sensor with Dimming/Occupancy/Daylight Harvesting and Enlighted Connected System⁽⁶⁾

ZENLI

Enlighted Micro Sensor with Dimming/Occupancy/Daylight Harvesting and Enlighted IoT System⁽⁶⁾

D10

10' Dual Circuit Cord

P(NEMA)

Plug (Specify NEMA configuration)

CC

Conformal Coating

LVL

0-10V Dimming Leads for Easy Field Access

Emergency Pack - Up to 8W⁽⁸⁾

EM2

Emergency Pack - Up to 16W⁽⁸⁾

QWH(_) Quick Wire Harness⁽⁹⁾

Aligner Clips for Continuous Row Mounting

BAA Buy American Act Compliant





Schematic:





Length (L) = 36.00" Width (W) = 2.50" Height (H) = 2.165"



The ECLN features field replaceable boards and drivers. This allows you to upgrade to more efficient technology in the future. Or, in the rare event of a failure, you can rapidly replace defective components. Re-boardABILITY helps to ensure you won't get stuck with an obsolete light fixture. <u>Learn more about Re-boardABILITY here.</u>

Performance Chart:


Catalog #	Lumens			Catalog #	Lumens	Watts	LPW	Cata
ECL N 3 LW UV FR 835	1538	12	123.8	ECL N 3 LW UV FR 840	1589	12	127.9	ECL
ECL N 3 MD UV FR 835	3032	23	134.5	ECL N 3 MD UV FR 840	3132	23	139.0	ECL

Catalog #	Lumens	Watts	LPW
ECL N 3 LW UV FR 850	1637	12	131.7
ECL N 3 MD UV FR 850	3226	23	143.1

Scaling Factor: No lens: 1.05

Photometric Data:

Relative Luminous Intensity







Douglas Lighting Controls, Inc.: Cloud-based controls

The ECLN can be equipped with the Douglas Bluetooth Intelligent Fixture Sensor (IFS) as well as the Intelligent Fixture Controller.

IFS



- Occupancy, vacancy, partial-on and partial-off
- Occupancy timeout adjustable from 5 to 90 minutes
- Primary and secondary daylight harvesting

IFC



- Listed for emergency control when used on dedicated emergency power bus
- Same occupancy and daylight controls as the IFS when networked with one or more IFS sensors

Available with both IFS and IFC:

- 0-10V dimming with dim-to-off
- Bluetooth beacon for digital ceiling, IoT and location service strategies
 - 150-foot clear line of sight, 50 feet through standard walls
- May be used with dual-channel, tunable white LED drivers providing auxiliary power and dimto-off capability
- Commissioning through Douglas Lighting Controls, Inc. app from Apple app store **Note:** Additional equipment required for IoT capabilities; max mounting height for sensor: 16.4 ft

CheckLight® Energy Management System

Douglas controls can be integrated with the CheckLight® Energy Management system. This system can help you uncover energy conversion opportunities, create conservation strategies, analyze lighting load inefficiencies, and make configuration changes from anywhere with Douglas' user-friendly interface. You can get measurements, reports, and control your system from a web-based application.

CheckLight® has the capability to look at different facilities within a portfolio and use data benchmarks to compare building performances.

- Find energy conservation opportunities
- Create energy saving strategies
- Analyze load inefficiencies
- Optimize energy management

Enlighted: All-in-one sensors, upgradeable systems

Enlighted's SMART Micro Sensor is an all-in-one unit: task tuning, high-end trimming, daylight harvesting, and occupancy/vacancy detection. Max installation height is 15 feet.

Enlighted sensors come standard with the Enlighted One system (the "ZENLO" option). Enlighted Connected ("ZENLC") offers even more options. The Enlighted IoT ("ZENLI") option allows the full implementation of Enlighted's services. Each system can be fully upgraded to the next tier in the future. So if you start with Enlighted One but want to add energy reporting or building management systems integration in the future, you can.



Enlighted Capabilities*	Enlighted One (ZENLO)	Enlighted Connected (ZENLC)	Enlighted IoT (ZENLI)
Motion and Switch Groups	✓	✓	✓
Daylight Harvesting	✓	✓	✓
Schedule Lighting		✓	✓
Energy Reporting & Optimization		✓	✓
Environment Data & Lighting Controls API		✓	✓
Building Management System Integration		✓	✓
Where & Space Applications			✓
Location & Occupancy APIs & Beaconing			✓
Future App & API Ready			✓

Note: Additional equipment required for ZENLC and ZENLI

Real-time data analytics

Enlighted's control units compile data in real-time, which can be viewed via the Energy Manager. The Energy Manager is part of the Enlighted Connected and Enlighted IoT configurations.

- Real-time measurements and verification of energy savings
- Space analytics data can be compiled into motion trails and heat maps
- Analyze traffic density and congestion in a space



Learn more about our available advanced controls options here:

www.lumenfocus.com/controls-overview

© 2021 Enlighted for all Enlighted content and images.

© 2021 Douglas Lighting Controls, Inc. for all Douglas content and images. The Bluetooth® word, mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Douglas Lighting Controls is under license. Other trademarks and trade names are those of their respective owners.





Other controls available:



Dimming Sensors (Z211/Z311)

- The Wattstopper FSP sensor provides multi-level control based on motion and/or daylight contribution
- · Comes pre-installed on the fixture
- · Rated for cold locations
- Parameters for Bluetooth-enabled Z311 adjustable via phone app iOS or Android
- Parameters for Z211 adjustable via wireless configuration tool (FSIR-100 sold separately)
- Available with black lens for black finishes (pictured right)
- Three lenses available, tailored for the ideal detection area and mounting height:
 - L2: 360° lens, maximum coverage 48′, diameter from 8′ height
 - L3: 360° lens, maximum coverage 40′, diameter from 20′ height

Leviton Intellect Solo PIR Sensor (ZSOL)

The ECLN can be equipped with an integrated Leviton Intellect Solo Sensor ("ZSOL" option). This is a 0-10V dimming Passive Infrared (PIR) occupancy and daylight harvesting





Other features:

- Partial-on
- Partial-off
- 8' to 10' mounting height
- IP20 rated
- Detection angle: 120 degrees
- IR remote available for

programming sensor from the floor (sold separately)

• Can be used to comply with IECC, ASHRAE 90.1 and 2019 Title 24, Part 6 dimming, occupancy/vacancy sensing and daylight harvesting requirements.


Microwave Occupancy Sensor (ZOSMD)

The Leviton OSM3D-V1W (or equivalent) detects motion through low density materials using high frequency electromagnetic waves. This means it can sit discretely behind the ECLN's frosted lens. The ZOSMD features automatic switching based on motion and ambient light level. ZOSMD option adds step-dimming functionality - standby dimming level 10% / 20% / 30% / 50%.



Max mounting height for ZOSMD 49 feet.

Other Options:



Shielding Frosted acrylic diffuser lenses minimize glare and improve aesthetics.



Conformal coating Grants LED boards added protection from moisture and corrosion in more hazardous environments.



Cords are available in single circuit or dual circuit, 6' or 10'. Standard plug is optional, as are other NEMA configurations if specified.



Hanging The QC hanging kit from ALP comes in 10' or 20'. Cables are pre-looped for easy installation and designed for easy fixture height adjustment. When ordered, QCs come boxed with each fixture.

